



# GE Oil & Gas - HSR Compressor Performance Report

Project Name:  
 Customer/End-user: CIOC 9-3-68-4w/6  
 Packager:  
 Site Location:

GE ID#: 141218-094411-GA4  
 Case #: n/a  
 Version: 02.02.00  
 Date: 19/12/2014, 7:18:04 PM

Application Data:	Compressor Frame: M302	Driver Data:	Site Data:
Est. Flow:: <b>0.442 MMscfd</b>	Rated Power: 120.0 HP	Type: Engine	Elevation: 0.291 ft
Load/Flow: <b>150.3 HP/MMscfd</b>	Stroke: 3.000 in	Manufacturer: Caterpillar	Atm. Pressure: 14.6960 psiA
Est. Total Load: <b>66.4 HP (79%)</b>	Rated Speed: 1800	Model: G3304-NA	Ambient Temp: 80.0 deg F
Run Speed: <b>1800</b>	Rod Diameter: 1.125 in	Rated Power: 95.0 HP	Gas Method: <b>Generic</b>
Auxiliary Load: 11.0 HP(d)	Max Rod Load Comp: 6000 lbf	Rated Speed: 1800	<b>Base Conditions for Flow Rates:</b>
Lubrication: Lubed	Max Rod Load Tens: 6000 lbf	Avail. Power: 84.0 HP	Pressure: 14.6960 psiA
Type: Miscellaneous	Max Rod Load Gas: 6000 lbf	Amb. Derate: Fixed	Temperature: 60.0 deg F
<b>ISSUES:</b> -			
Project Notes: No Gas Analysis Entered,			
Case Notes:			
Order Status:			

Stage/Service Data:	Stage-1	Stage-2
Flow Rate: MMscfd	0.44	0.44
Load: HP	33.5	28.9
Specific Gravity: -	0.6500	0.6500
K Value (Cp/Cv): -	1.2400	1.2400
Zs: -	0.9928	0.9800
Zd: -	0.9896	0.9753
Suction Press.: psiG	30.00	141.52
Ps@Flange: psiG	28.66	141.52
Pd@Flange: psiG	146.21	459.29
Discharge Press.: psiG	141.52	450.00
Compress. Ratio: -	3.7113	3.0341
Suction Temp.: deg F	40.0	80.0
Cooler Temp.: deg F	80.0	n/a

Cylinder Data:	Throw-1	Throw-2	Throw-3	Throw-4	Throw-5	Throw-6
Model: -	M-Series	M-Series				
Operating Mode: -	D/A Cyl	D/A Cyl				
<b>Head End</b>	<b>Stage</b>	<b>Stg-1</b>	<b>Stg-2</b>	-	-	-
Bore: in	5.5	3				
MAWP: psiG	1000	1440				
RDP: psiG	909	1309				
Tail Rod Dia: in	0	0				
Est. Td: deg F	199.8	220.6				
VVCP Open: in : Turns	0.00 : 0	0.00 : 0				
Base Clr: %	15.28	15.99				
Added Clr: %	0.00	0.00				
Total Clr: %	15.28	15.99				
Vol. Eff. Suct.: %	67.67	73.79				
Vol. Eff. Disch.: %	23.43	30.00				
Flow: MMscfd	0.22	0.24				
<b>Crank End</b>	<b>Stage</b>	<b>Stg-1</b>	<b>Stg-2</b>	-	-	-
Bore: in	5.5	3				
MAWP: psiG	1000	1440				
RDP: psiG	909	1309				
Est. Td: deg F	199.8	220.6				
Base Clr: %	13.38	18.10				
Added Clr: %	0.00	0.00				
Total Clr: %	13.38	18.10				
Vol. Eff. Suct.: %	71.09	70.82				
Vol. Eff. Disch.: %	24.61	28.79				
Flow: MMscfd	0.22	0.20				
Valve Spacers: HE#/CE#	0 / 0	0 / 0				
<b>Rod Loads</b>						
Gas-Compress.: %	52.7	43.6				
Gas-Tension: %	48.9	33.0				
Net-Compress.: %	31.6	33.8				
Net-Tension: %	28.2	30.4				
Pin Reversal: Deg/Mag%	n/a	n/a				
<b>Throw Loading</b>	<b>HP</b>	33.5	28.9			

**BOLD = Out of Limit** FILE: Program.hsr

GE HSR Compressors, its owners, affiliates, authorized distributors or agents assume no liability for any consequences, damages or loss of production as a result of use or misuse of the information or calculations contained in this program.